

### STATE LEVEL ENVIRONMENT IMPACT ASSESSMENT AUTHORITY

Environment department, Room No. 217, 2nd floor, Mantralaya, Annexe, Mumbai- 400 032. Date:July 20, 2020

To.

### Mr.Prakash Bhikamchand Chhajed

at S.No 40/4B(P) & 41/3A/1(P) , Near Vimal Garden

Subject: Environment Clearance for Proposed Construction project by M/s Vardhaman Associates

Sir,

This has reference to your communication on the above mentioned subject. The proposal was considered as per the EIA Notification - 2006, by the State Level Expert Appraisal Committee-III, Maharashtra in its 94th meeting and recommend the project for prior environmental clearance to SEIAA. Information submitted by you has been considered by State Level Environment Impact Assessment Authority in its 182nd meetings.

2. It is noted that the proposal is considered by SEAC-III under screening category 8(a) as per EIA Notification 2006.

### Brief Information of the project submitted by you is as below:-

1.Name of Project	"Residential & Commercial"
2.Type of institution	Private
3.Name of Project Proponent	Mr.Prakash Bhikamchand Chhajed
4.Name of Consultant	M/s JV Analytical Services
5.Type of project	Residential & Commercial
6.New project/expansion in existing project/modernization/diversification in existing project	New Project
7.If expansion/diversification, whether environmental clearance has been obtained for existing project	Not applicable
8.Location of the project	S.No 40/4B(P) & 41/3A/1(P) , Near Vimal Garden
9.Taluka	Haveli
10.Village	Rahatani
Correspondence Name:	Mr.Prakash Bhikamchand Chhajed
Room Number:	
Floor:	analaonta
Building Name:	Sai Niwas,Near Jyotiba mangal Karyalay
Road/Street Name:	-
Locality:	Kalewadi
City:	Pune-411017
11.Whether in Corporation / Municipal / other area	Pimpri Chinchwad Municipal Corporation
42.422.422	Received
12.IOD/IOA/Concession/Plan Approval Number	IOD/IOA/Concession/Plan Approval Number: BP/Env/Rahatani/02/2019 ,Date- 15.02.2019
K E	Approved Built-up Area: 52346.26
13.Note on the initiated work (If applicable)	NA NA

SEIAA Meeting No: 182 Meeting Date: December 6, 2019 ( SEIAA-STATEMENT-0000003187 ) SEIAA-MINUTES-0000002790 SEIAA-EC-0000002318

Page 1 of 16

Shri. Anil Diggikar (Member Secretary SEIAA)

Con.

14.LOI / NOC / IOD from MHADA/ Other approvals (If applicable)	Applicable-2705.69 m2			
15.Total Plot Area (sq. m.)	14750.00 m2			
16.Deductions	1568.73 m2			
17.Net Plot area	13181.27 m2			
	FSI area (sq. m.): 26528.22 m2			
18 (a).Proposed Built-up Area (FSI & Non-FSI)	Non FSI area (sq. m.): 25818.04 m2			
	Total BUA area (sq. m.): 52346.26			
	Approved FSI area (sq. m.): 26528.22			
18 (b).Approved Built up area as per DCR	Approved Non FSI area (sq. m.): 25818.04			
	Date of Approval: 15-02-2019			
19.Total ground coverage (m2)	3809.94 m2			
20.Ground-coverage Percentage (%) (Note: Percentage of plot not open to sky)	25.83 % of Total Plot area (14750.00 m2) & 28.90 % of Net Plot area (13181.27 m2)			
21.Estimated cost of the project	1150000000			



## Government of Maharashtra

			22.F	roduct	ion Details				
Serial Number	Pro	oduct Existing		(MT/M)	Proposed (MT/M)	Total (MT/M)			
1	Not ap	plicable	Not app	plicable	icable Not applicable Not applicable				
		2	3.Tota	l Wate	r <mark>Requiremen</mark> t				
Source of water Fresh water (CMD): Recycled water - Flushing (CMD):		PCMC							
		Fresh wate	r (CMD):	335.54 m3/	day (One time)				
				126.81 m3/	day				
		Recycled w Gardening		12.00 m3/d	ay				
		Swimming make up ((		2.00 m3/da	Yes				
Dry season:		Total Wate Requireme :		196.73 m3/	day	Z <u>E</u>			
		Fire fighting Undergrout tank(CMD)	nd water	300 m3					
		Fire fighting Overhead value (CMD)	water	120 m3					
		Excess trea	ated water	150.57 m3/day					
		Source of v	1/0	PCMC	B R				
		Fresh wate	7.7.2	323.54 m3/day (One time)					
		Recycled w Flushing (	CMD):	126.81 m3/day					
		Recycled w Gardening	(CMD):	NA					
		Swimming make up ((	-	2.00 m3/day					
Wet season:		Total Wate Requireme		196.73 m3/day					
tank(CMD):  Fire fighting - Overhead water tank(CMD):  Excess treated water  Dimension of Swimming Size of Kids Pool -3.0m x Total water Requiremen Make up Water requiremen Make up Water requiremen Details of Plant & Machi		Undergrou	nd water	300 m3					
		Overhead v	water	120 m3 12 S N 1 7 2					
		162.57 m3/day							
		x 6m x 0.6m at: 82,600 lit ment in KLD inery used for achieved for Capital cost a Lakh	: : 2.00 m3/day or treatment of Swimming swimming pool water and						

		2	4.Detail	s of Tota	l water o	onsume	d			
Particula rs	Consumption (CMD)		Loss (CMD)			Effluent (CMD)				
Water Require ment	Existing	Proposed	Total	Existing	Proposed	Total	Existing	Proposed	Total	
Domestic	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
		Level of th		4.00 m to 6	.00 m BGL					
		Size and n tank(s) an Quantity:	o of RWH	NA	HOZ	×12-				
		Location o tank(s):	f the RWH	NA do	विधिक्य		7			
25.Rain V		Quantity o pits:	f recharge	08 Nos.	6	301:	34			
Harvestii (RWH)	ıg	Size of rec	harge pits	2.5 m x 2.5	m x 3.0 m d	epth A	(3)			
		Budgetary (Capital co	allocation st) :	Rs. 20.00 Lakh						
		Budgetary (O & M cos		Rs. 0.40 Lakh/Year						
		Details of if any:	UGT tanks	Domestic UG tank Capacity: 312.10 m3 Flushing UG tank Capacity: 208.20 m3 Fire UG tank Capacity:300.00 m3						
		2/	7110	_	0	4	12.			
26.61		Natural wa drainage p		/ज्यस्य	ा मुद्रा :		7			
26.Storm drainage	water	Quantity o water:	f storm	106.93 m3/day						
		Size of SW	D:	600 mm dia	a.					
	Sewage generation in KLD:		289.38 m3/	day	eni					
		STP technology:		MBBR						
27.Sewage and Waste water		Capacity o (CMD):	f STP	1 No. of 300 m3/day						
		Location & the STP:	area of	129.00 m2	129.00 m2					
			allocation st):	Rs.86.00 La	akh					
		Budgetary (O & M cos		Rs.15.71 La	akh/Year					

	28.Solid waste Management				
Waste generation in	Waste generation:	40 kg/day			
the Pre Construction Disposal of the		Use for Leveling			
	Dry waste:	646.00 kg/day			
	Wet waste:	703.00 kg/day			
Waste generation	Hazardous waste:	NA			
in the operation Phase:	Biomedical waste (If applicable):	NA			
	STP Sludge (Dry sludge):	44.6 kg/day			
	Others if any:	NA			
	Dry waste:	Authorized Vender			
	Wet waste:	Organic Waste Convertor			
	<b>Hazardous waste:</b>	NA SA			
Mode of Disposal of waste:	Biomedical waste (If applicable):	NA OF THE PROPERTY OF THE PROP			
	STP Sludge (Dry sludge):	Used as Manure after treatment in OWC			
	Others if any:	NA			
	Location(s):	在反			
Area requirement:	Area for the storage of waste & other material:	91.00 m2 including machinery area			
	Area for machinery:	Included in other material area			
Budgetary allocation (Capital cost and	Capital cost:	Rs. 20.75 Lakh			
O&M cost):	O & M cost:	Rs. 4.29 Lakh/Year			

# Government of Maharashtra

	29.Effluent Charecterestics							
Serial Number	Parameters	Unit	Inlet Effluent Charecterestics	Outlet Effluent Charecterestics	Effluent discharge standards (MPCB)			
1	NA	NA	NA	NA	NA			
Amount of effluent generation (CMD):		NA			•			
Capacity of	the ETP:	NA						
Amount of t recycled:	reated effluent	NA						
Amount of v	vater send to the CETP:	NA						
Membership	o of CETP (if require):	NA						
Note on ETP technology to be used NA								
Disposal of	the ETP sludge	NA						



### Government of Maharashtra

			30.Ha	zardous	Waste D	etails		
Serial Number	Descr	iption	Cat	UOM	Existing	Proposed	Total	Method of Disposal
1	N	ΙA	NA	NA	NA	NA	NA	NA
			31.St	acks em	ission De	etails		
Serial Number	rial Section & units Fuel Use			Stack No.	Height from ground level (m)	Internal diameter (m)	Temp. of Exhaust Gases	
1	140 KV	A - 1No.	HSD-27.5 100%		S-1	5.6 Mtr.	will be provided	will be provided
2	100 KV	A - 1 No.	HSD- 21.9 100%		S-2	5.0 Mtr.	will be provided	will be provided
3	40 KVA	A - 1No.	HSD- 6.5 100%	Ltr/Hr @ load	S-3	4.0 Mtr.	will be provided	will be provided
		7	32.De	tails of I	Tuel to be	e used	仌	
Serial Number	Туг	oe of Fuel	50	Existing		Proposed	VI)	Total
1		HSD		NA	5 1	55.9 Ltr/Hr		55.9 Ltr/Hr
33.Source o	f Fuel	田、	Bhara	at Petroleum	Corporation	Ltd/ Hindus	stan Petroleu	ım
34.Mode of Transportation of fuel to site By Roadway								
		呂	廿			10	F	
		8	27	35.E	nergy	15		
		Source of participation supply:	power	MSEDCL.		S. E	FF.	
		During Cor Phase: (De Load)		30 KW				
	DG set as Power back-up during construction p		ıring	40 KVA- 1 No				
Dox	During Operation phase (Connected load):		2210 KW					
_	Power requirement:  During Operation phase (Demand load):  Transformer:  DG set as Power back-up during operation phase			1169 KW				
			er:	22/630 KVA	A – 2 Nos.			
			ıring	140 KVA - 1 No.(Resi.), 100 KVA - 1 No.(Comm.) & 40 KVA - 1No.(MHADA)				
		Fuel used:		HSD				
		Details of I tension lin through thany:	e passing	No	No			
		Energ	gy saving	j by non-	-convent	ional me	thod:	

Page 7 of 16 | SEI

- Solar water heating systems will be done for bathrooms.
- Solar lights will be provided for common amenities like Street lighting & Garden lighting.
- LED based lighting will be done in the common areas, landscape areas, signage's, entry gates and boundary compound walls etc.
- Auto Timer switches will be provided for Street lights, Garden lights, Parking & staircase Lights & other common area Lights, for saving electrical energy.
- Water level controllers with timers will be used for Water pumps.
- To create awareness to end consumer or flat owner, for using energy efficient light fittings LED lights.

### **36.Detail calculations & % of saving:**

Serial Number	Energy Conservation Measures	Saving %
1	Percentage Savings Per Day. For Total Annual Savings in KWH for Solar Power, Hot Water & LED Lighting Details	17.69 %
2	Percentage Savings Per Day. For Total Annual Savings in KWH For Solar Power & Solar Hot Water Details	13.7 %

### 37. Details of pollution control Systems

Source	Existing pollution control system	Proposed to be installed
Air		Green belt will be provided
Water	图片 () ()	STP will be installed & excess treated water used for flushing & gardening
Noise	THE	Noise monitoring will be done in once a fortnight.  Traffic management plan to be prepared. Acoustically enclosed DG set will be brought & installed.
Solid Waste		Wet Waste will be treated in OWC. STP sludge will be Used as Manure after treatment in OWC Dry Waste will be given to SWACH

Budgetary allocation	Capital cost:	Energy system : Rs.56.70 Lakh
(Capital cost and O&M cost):	O & M cost:	Energy system: Rs. 1.13 Lakh/Year

### 38.Environmental Management plan Budgetary Allocation

### a) Construction phase (with Break-up):

Serial Number	Attributes	Parameter	Total Cost per annum (Rs. In Lacs)
1	Air Environment	Water for Dust Suppression, Air & Noise Monitoring	0.50 Lakh/Year
2	Water Environment	Tanker Water for Construction, Water Monitoring	0.50 Lakh/Year
3	Land Environment	Site Sanitation -Mobile toilets	0.50 Lakh/Year
4 Socio-economic Control, Fit Facilities, I Check Up, C For Children, children, Pe		Disinfection- Pest Control, First Aid Facilities, Health Check Up, Creches For Children, Food for children, Personal Protective Equipment	1.00 Lakh/Year

### b) Operation Phase (with Break-up):

Serial Number Component	Description	Capital cost Rs. In Lacs	Operational and Maintenance cost (Rs. in Lacs/yr)
----------------------------	-------------	-----------------------------	---

**Page 8 of 16** 

1	STP	300 m3/day	Rs.86.00 Lakh	Rs.15.71 Lakh/Year
2	RWH	Rain water Harvesting	Rs.20.00 Lakh	Rs.0.40 Lakh/Year
3	MSW	OWC	Rs.20.75 Lakh	Rs.4.29 Lakh/Year
4	Energy System	-	Rs.56.70 Lakh	Rs.1.13 Lakh / Year
5	Landscaping	-	Rs.50.00 Lakh	Rs.5.00 Lakh/Year
6	Swimming Pool	-	Rs.14.27 Lakh	Rs.1.68 Lakh/Year
7	Safety Equipments	-	Rs.10.00 Lakh	Rs.2.00 Lakh/Year
8	Post EC Monitoring	-	-	Rs.2.50 Lakh/Year
9	Dry Waste Management	-	-	Rs.2.80 Lakh/Year

### 39.Storage of chemicals (inflamable/explosive/hazardous/toxic substances)

Description	Status	Location	Storage Capacity in MT	Maximum Quantity of Storage at any point of time in MT	Consumption / Month in MT	Source of Supply	Means of transportation
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
	国	40.Any Ot	her Info	rmation	市员		

No Information Available

## Government of Maharashtra

SEIAA Meeting No: 182 Meeting Date: December 6, 2019 ( SEIAA-STATEMENT-0000003187 ) SEIAA-MINUTES-0000002790 SEIAA-EC-0000002318

Page 9 of 16 SE

CRZ/ RRZ clearance obtain, if any:	NA
Distance from Protected Areas / Critically Polluted areas / Eco-sensitive areas/ inter-State boundaries	NA
Category as per schedule of EIA Notification sheet	8(a)
Court cases pending if any	NA
Other Relevant Informations	HTO SHOTAN
Have you previously submitted Application online on MOEF Website.	No ववार्थ का अपने किया किया किया किया किया किया किया किया
Date of online submission	

3. The proposal has been considered by SEIAA in its 182nd meeting & decided to accord environmental clearance to the said project under the provisions of Environment Impact Assessment Notification, 2006 subject to implementation of the following terms and conditions:

### **Specific Conditions:**

I	PP to upload revised energy saving calculations.
II	PP to ensure that CER plan gets approved from Municipal Commissioner/District Collector.
III	PP Shall comply with Standard EC conditions mentioned in the Office Memorandum issued by MoEF & CC vide F.No.22-34/2018-IA.III dt.04.01.2019.
IV	SEIAA decided to grant EC for -FSI:26528.22 m2, Non-FSI: 25818.04 m2 and Total BUA:52346.26 m2 ( Plan Approval no-BP/ENV/Rahatani/02/2019, Date-15.02.2019)
V	PP to upload revised energy saving calculations.
VI	PP to ensure that CER plan gets approved from Municipal Commissioner/District Collector.
VII	PP Shall comply with Standard EC conditions mentioned in the Office Memorandum issued by MoEF & CC vide F.No.22-34/2018-IA.III dt.04.01.2019.
VIII	SEIAA decided to grant EC for -FSI:26528.22 m2, Non-FSI: 25818.04 m2 and Total BUA:52346.26 m2 ( Plan Approval no-BP/ENV/Rahatani/02/2019, Date-15.02.2019)

### General Conditions:

ocherui conditions.	~4 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
I	E-waste shall bedisposed through Authorized vendor as per E-waste (Management and Handling) Rules, 2016.
П	The Occupancy Certificate shall be issued by the Local Planning Authority to the project only after ensuring sustained availability of drinking water, connectivity of sewer line to the project site and proper disposal of treated water as per environmental norms.
ш	This environmental clearance is issued subject to obtaining NOC from Forestry & Wild life angle including clearance from the standing committee of the National Board for Wild life as if applicable & this environment clearance does not necessarily implies that Forestry & Wild life clearance granted to the project which will be considered separately on merit.
IV	PP has to abide by the conditions stipulated by SEAC& SEIAA.
v	The height, Construction built up area of proposed construction shall be in accordance with the existing FSI/FAR norms of the urban local body & it should ensure the same along with survey number before approving layout plan & before according commencement certificate to proposed work. Plan approving authority should also ensure the zoning permissibility for the proposed project as per the approved development plan of the area.
VI	If applicable Consent for Establishment" shall be obtained from Maharashtra Pollution Control Board under Air and Water Act and a copy shall be submitted to the Environment department before start of any construction work at the site.

Page 10 of 16

VII	All required sanitary and hygienic measures should be in place before starting construction activities and to be maintained throughout the construction phase.
VIII	Adequate drinking water and sanitary facilities should be provided for construction workers at the site. Provision should be made for mobile toilets. The safe disposal of wastewater and solid wastes generated during the construction phase should be ensured.
IX	The solid waste generated should be properly collected and segregated. dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material.
X	Disposal of muck during construction phase should not create any adverse effect on the neighboring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
XI	Arrangement shall be made that waste water and storm water do not get mixed.
XII	All the topsoil excavated during construction activities should be stored for use in horticulture / landscape development within the project site.
XIII	Additional soil for leveling of the proposed site shall be generated within the sites (to the extent possible) so that natural drainage system of the area is protected and improved.
XIV	Green Belt Development shall be carried out considering CPCB guidelines including selection of plant species and in consultation with the local DFO/ Agriculture Dept.
XV	Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
XVI	Construction spoils, including bituminous material and other hazardous materials must not be allowed to contaminate watercourses and the dumpsites for such material must be secured so that they should not leach into the ground water.
XVII	Any hazardous waste generated during construction phase should be disposed off as per applicable rules and norms with necessary approvals of the Maharashtra Pollution Control Board.
XVIII	The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environments (Protection) Rules prescribed for air and noise emission standards.
XIX	The diesel required for operating DG sets shall be stored in underground tanks and if required, clearance from concern authority shall be taken.
XX	Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
XXI	Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB/MPCB.
XXII	Fly ash should be used as building material in the construction as per the provisions of Fly Ash Notification of September 1999 and amended as on 27th August, 2003. (The above condition is applicable only if the project site is located within the 100Km of Thermal Power Stations).
XXIII	Ready mixed concrete must be used in building construction.
XXIV	Storm water control and its re-use as per CGWB and BIS standards for various applications.
XXV	Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
XXVI	The ground water level and its quality should be monitored regularly in consultation with Ground Water Authority.
XXVII	The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the MPCB and Environment department before the project is commissioned for operation. Discharge of this unused treated affluent, if any should be discharge in the sewer line. Treated effluent emanating from STP shall be recycled/refused to the maximum extent possible. Discharge of this unused treated affluent, if any should be discharge in the sewer line. Treatment of 100% gray water by decentralized treatment should be done. Necessary measures should be made to mitigate the odour problem from STP.
XXVIII	Permission to draw ground water and construction of basement if any shall be obtained from the competent Authority prior to construction/operation of the project.
XXIX	Separation of gray and black water should be done by the use of dual plumbing line for separation of gray and black water.
XXX	Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.
XXXI	Use of glass may be reduced up to 40% to reduce the electricity consumption and load on air conditioning. If necessary, use high quality double glass with special reflective coating in windows.

XXXII	Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.
XXXIII	Energy conservation measures like installation of CFLs /TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible like installing solar street lights, common solar water heaters system. Project proponent should install, after checking feasibility, solar plus hybrid non-conventional energy source as source of energy.
XXXIV	Diesel power generating sets proposed as source of backup power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Use low sulphur diesel. The location of the DG sets may be decided with in consultation with Maharashtra Pollution Control Board.
XXXV	Noise should be controlled to ensure that it does not exceed the prescribed standards. During nighttime the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.
XXXVI	Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.
XXXVII	Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code, which is proposed to be mandatory for all air-conditioned spaces while it is aspiration for non-air-conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
XXXVIII	The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.
XXXIX	Regular supervision of the above and other measures for monitoring should be in place all through the construction phase, so as to avoid disturbance to the surroundings.
XL	Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.
XLI	Six monthly monitoring reports should be submitted to the Regional office MoEF, Bhopal with copy to this department and MPCB.
XLII	Project proponent shall ensure completion of STP, MSW disposal facility, green belt development prior to occupation of the buildings. As agreed during the SEIAA meeting, PP to explore possibility of utilizing excess treated water in the adjacent area for gardening before discharging it into sewer line No physical occupation or allotment will be given unless all above said environmental infrastructure is installed and made functional including water requirement in Para 2. Prior certification from appropriate authority shall be obtained.
XLIII	Wet garbage should be treated by Organic Waste Converter and treated waste (manure) should be utilized in the existing premises for gardening. And, no wet garbage will be disposed outside the premises. Local authority should ensure this.
XLIV	Local body should ensure that no occupation certification is issued prior to operation of STP/MSW site etc. with due permission of MPCB.
XLV	A complete set of all the documents submitted to Department should be forwarded to the Local authority and MPCB.
XLVI	In the case of any change(s) in the scope of the project, the project would require a fresh appraisal by this Department.
XLVII	A separate environment management cell with qualified staff shall be set up for implementation of the stipulated environmental safeguards.
XLVIII	Separate funds shall be allocated for implementation of environmental protection measures/EMP along with item-wise breaks-up. These cost shall be included as part of the project cost. The funds earmarked for the environment protection measures shall not be diverted for other purposes and year-wise expenditure should reported to the MPCB & this department.
XLIX	The project management shall advertise at least in two local newspapers widely circulated in the region around the project, one of which shall be in the Marathi language of the local concerned within seven days of issue of this letter, informing that the project has been accorded environmental clearance and copies of clearance letter are available with the Maharashtra Pollution Control Board and may also be seen at Website at http://ec.maharashtra.gov.in.
L	Project management should submit half yearly compliance reports in respect of the stipulated prior environment clearance terms and conditions in hard & soft copies to the MPCB & this department, on 1st June & 1st December of each calendar year.
LI	A copy of the clearance letter shall be sent by proponent to the concerned Municipal Corporation and the local NGO, if any, from whom suggestions/representations, if any, were received while processing the proposal. The clearance letter shall also be put on the website of the Company by the proponent.

LII	The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM. SO2, NOx (ambient levels as well as stack emissions) or critical sector parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.
LIII	The project proponent shall also submit six monthly reports on the status of compliance of the stipulated EC conditions including results of monitored data (both in hard copies as well as by e-mail) to the respective Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB.
LIV	The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the respective Regional Offices of MoEF by e-mail.
LV	E-waste shall bedisposed through Authorized vendor as per E-waste (Management and Handling) Rules, 2016.
LVI	The Occupancy Certificate shall be issued by the Local Planning Authority to the project only after ensuring sustained availability of drinking water, connectivity of sewer line to the project site and proper disposal of treated water as per environmental norms.
LVII	This environmental clearance is issued subject to obtaining NOC from Forestry & Wild life angle including clearance from the standing committee of the National Board for Wild life as if applicable & this environment clearance does not necessarily implies that Forestry & Wild life clearance granted to the project which will be considered separately on merit.
LVIII	PP has to abide by the conditions stipulated by SEAC& SEIAA.
LIX	The height, Construction built up area of proposed construction shall be in accordance with the existing FSI/FAR norms of the urban local body & it should ensure the same along with survey number before approving layout plan & before according commencement certificate to proposed work. Plan approving authority should also ensure the zoning permissibility for the proposed project as per the approved development plan of the area.
LX	If applicable Consent for Establishment" shall be obtained from Maharashtra Pollution Control Board under Air and Water Act and a copy shall be submitted to the Environment department before start of any construction work at the site.
LXI	All required sanitary and hygienic measures should be in place before starting construction activities and to be maintained throughout the construction phase.
LXII	Adequate drinking water and sanitary facilities should be provided for construction workers at the site. Provision should be made for mobile toilets. The safe disposal of wastewater and solid wastes generated during the construction phase should be ensured.
LXIII	The solid waste generated should be properly collected and segregated. dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material.
LXIV	Disposal of muck during construction phase should not create any adverse effect on the neighboring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
LXV	Arrangement shall be made that waste water and storm water do not get mixed.
LXVI	All the topsoil excavated during construction activities should be stored for use in horticulture / landscape development within the project site.
LXVII	Additional soil for leveling of the proposed site shall be generated within the sites (to the extent possible) so that natural drainage system of the area is protected and improved.
LXVIII	Green Belt Development shall be carried out considering CPCB guidelines including selection of plant species and in consultation with the local DFO/ Agriculture Dept.
LXIX	Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
LXX	Construction spoils, including bituminous material and other hazardous materials must not be allowed to contaminate watercourses and the dumpsites for such material must be secured so that they should not leach into the ground water.
LXXI	Any hazardous waste generated during construction phase should be disposed off as per applicable rules and norms with necessary approvals of the Maharashtra Pollution Control Board.
LXXII	The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environments (Protection) Rules prescribed for air and noise emission standards.
	The diesel required for operating DG sets shall be stored in underground tanks and if required, clearance

Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to personal properties only during non-peak hours.   Ambient noise levels should conform to peak hours.		
pollution loads on the ambient air and noise quality should be closely monitored during construction phase.  Adequate measures should be be and to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCR/MPC/B.  Fly ash should be used as building material in the construction as per the provisions of Fly Ash Notification of September 1999 and amended as on 27th August, 2003. (The above condition is applicable only if the project site is located within the 100Km of Thermal Power Stations).  LXXVII Ready mixed concrete must be used in building construction.  LXXVII Storm water control and its re-use as per CGWB and BIS standards for various applications.  LXXX Determined the stationary of the standards for various applications.  LXXX The ground water level earlies in the standards for various applications.  LXXX The ground water level earlies in the standards for various applications.  LXXX The ground water level earlies in the standards for various applications.  LXXXI The ground water level earlies in the standards for various applications.  LXXXI The ground water level earlies in the standards for various applications.  LXXXI The installation of the Sewage Tractment Frant (SLTP) should be recruited for consultation with Ground Water Authority.  LXXXII The installation of the Sewage Tractment Frant (SLTP) should be restricted by an independent expert and a report in this report should be submitted to the MTGP and Engineering the properties of the sewer line. Treatment of The Sewage Tractment Frant (SLTP) should be recruited to the sewer line. Treatment of 100% gray water-by decadralized treatment should be done. Necessary measures should be made to mitigate the order ground water and construction of basement if any shall be obtained from the competent Authority from the construction of basement if any shall be obtained from the competent and liber's ground the sewage and the sewage	LXXIV	pollution check certificate and should conform to applicable air and noise emission standards and should be
LXXVII of September 1999 and amended as on 27th August, 2003. (The above condition is applicable only if the project site is located within the 100Km of Thermal Power Stations).  LXXVIII Ready mixed concrete must be used in building construction.  Storm water control and its re-use as per CGWB and BIS standards for various applications.  LXXIX Water Control and tis re-use as per CGWB and BIS standards for various applications.  LXXIX Water Control and the result of the standards for various applications.  LXXIX The ground water level and his great by the property of the standards for various applications.  LXXX The installation of the Sewede Treatment Plant   SIT  should be pertified by an independent expert and a report in this regard should be submitted to the MRCP and Environment department before the project is commissioned for operation Discharge of this unused treated affuent, if any should be discharge in the sewer line. Teaching official emanualing from STP shall be rejected affuent, if any should be discharge in the sewer line. Teaching official emanualing from STP shall be rejected affuent, if any should be discharge in the sewer line. Treating official emanualing from STP shall be rejected affuent, if any shall be obtained from the competent Authority prior to construction operation of the project.  LXXXII Permission for draw and black water should be done, by the use of dual pluphing line for separation of gray and black water should be done, by the use of dual pluphing line for separation of gray and black water should be done, by the use of dual pluphing line for separation of gray and black water should be done, by the use of dual pluphing line for separation of gray and black water should be done by the use of dual pluphing line for separation of gray and black water should be done to the electricity consumption and load on air conditioning. If necessary, size high chaling double class with spicial reductive coating in windows.  LXXXII Roof should receip prescriptive requirement as per Energy Co	LXXV	pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to
IXXIV   Storm water control and its re-use as per CGWB and BIS standards for various applications.	LXXVI	of September 1999 and amended as on 27th August, 2003. (The above condition is applicable only if the
Water demand during construction should be reduced by use of pre-mixed concrete, curring agents and other best practices referred.    The installation of this Sewage Transferred Plant (STP) should be restified by an independent expert and a report in this report is unused in the Plant (STP) should be restified by an independent expert and a report in this report in this report in the report of the unused in the received refused to the maximum extent possible. Discharge of this unused the discharge in the sewer line Treated of the office of the unused in the received refused to the maximum extent possible. Discharge of this unused the retail and under the sewer line Treated of the office of the propert.    IXXXII	LXXVII	Ready mixed concrete must be used in building construction.
LXXX The ground water level/and/sits quality should be monitored regularly in consultation with Ground Water Authority.  The installation of the Seward Prestment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the MPCP and Engironment department before the project is commissioned for operation. Discharge of this unused treated affluent, if any should be discharge in the sewer line. Treatment of 100% gray water by decediratized treatments from STP shall be recycled/retired to the maximum the sewer line. Treatment of 100% gray water by decediratized treatments should be once. Necessary messres should be made to mittgate the door problem from STP.  LXXXII Permission to draw ground water and construction of basement if any shall also obtained from the competent Authority prior to construction/operation of the project.  LXXXII Separation of gray and black water should be done by the use of dual plumbing line for separation of gray and black water.  LXXXIV Pixtures for showers, toiled flushing and drantaging should be of low flow ebhet by use of aerators or pressure reducing devices on sensor based control.  LXXXIV Use of glass may be heduced up to 10% to reduce the electricity consumption and load on air conditioning. If necessary, use high quality double glass with special reflective coating in wandows.  LXXXVI British of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed official for a per the previous proponent should install, after checking feasibility, solar plus playing apper proponent should install, after checking feasibility, solar plus playing apper the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed official for excepting apperl to the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed officiant for excepting ape	LXXVIII	
The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the MPCB and Environment department before the project is commissioned for operation. Discharge of this unused treated affilient, if any should be discharge in the sewer line. Freated efficient emanating from STP shall be recycled refused up to the sewer line. Treatment efficient emanating from STP shall be recycled refused to the maximum extent possible. Discharge of this unused treated affilient, if any should be discharge in the sewer line. Treatment of 100% gray water by deces, first part and construction of basement if any shall be obtained from the competent Authority Prior to construction/operation of the project.  LXXXIII  Permission to dray ground water and construction of basement if any shall be obtained from the competent Authority Prior to construction/operation of the project.  LXXXIII  Separation of gray and black water should be done by the use of dual plumbing line for separation of gray and plack water.  LXXXIII  Separation of gray and black water should be done by the use of dual plumbing line for separation of gray and plack water should be often by the use of dual plumbing line for separation of gray and plack water.  LXXXIII  Use of glass may be reduced up to 40% to reduce the electricity consumption and load on air conditioning. If necessary, use high quality double glass with special reflective coating in windows.  Roof should she present prior to fulfill requirement.  Energy conservation measures like installation of CELS /TELS for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use CTLs and TFLs should be properly collected and disposed diffsent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid interruly containmation. Use of solar panels may be done to the extent possible like installing solar street light	LXXIX	best practices referred.
report in this regard should be submitted to the NPCB and Brutroment before the project is commissioned for operation. Discharge of this unused terated affluent, aff any should be discharge in the sewer line. Treated effluent emanating from STP shall be recycled/refused to the maximum extent possible. Discharge of this unused treated affluent, if any should be discharge in the sewer line. Treatment of 100% gray water by deceinfulized treatment should be done. Necessary measures should be made to mitigate the odour problem from STP.  LXXXII  Permission to draw ground water and construction of basement if any shall be obtained from the competent Authority prior to construction/operation of the project.  Separation of gray and black water should be done by the use of dual plumbing line for separation of gray and black water.  EXXXIV  Fixtures for showers, toilet flushing and drinking should be of low flow ether by use of aerators or pressure reducing devices on sensor based control.  LXXXVI  Use of glass may be reduced by to 40% to reduce the electricity consumption and load on air conditioning. If necessarly use high quality double glass with special reflective coating in windows.  Roof should need prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.  Energy conservation measured like insulation of C.F.Ls. /TFLs. for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed offeren for recycling asper the prevailing quietleines/rules of the regulatory authority of avoid inerury contemination. Use of solar panels may be done to the extent possible like installing solar street lights, common solar water heaters system. Project proponent should install, after checking feasibility, solar plus hybrid non-conventional energy source as source of energy.  Diese power generating sets proposed as	LXXX	
Authority prior to construction/operation of the project.  Separation of gray and black water should be done by the use of dual plumbing line for separation of gray and black water.  LXXXIV  Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices of sensor based control.  LXXXV  Use of glass may be reduced up to 40% to reduce the ejectricity consumption and load on air conditioning. If necessary, use high quality double glass with special reflective coating in windows.  LXXXVI  Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to Huffill requirement.  Energy conservation measures like installation of CFLs /TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed off/sent for recycling appropriate to the extent possible like installating solar street lights, common solar water barers system. Project proponent should install, after checking feasibility, solar plus hybrid non-conventional energy source as source of energy.  Joiseal power generating sets proposed as source of backup power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act. 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets, Use low sulphur diesel. The location of the DG sets may be decided with in consultation with Maharashtra Pollution Control Board.  Noise should be controlled to ensure that it does not exceed the prescribed standards. During nighttime the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.  XCI  Traffic congestion near the entry and exit points from the roads a	LXXXI	report in this regard should be submitted to the MPCB and Environment department before the project is commissioned for operation. Discharge of this unused treated affluent, if any should be discharge in the sewer line. Treated effluent emanating from STP shall be recycled/refused to the maximum extent possible. Discharge of this unused treated affluent, if any should be discharge in the sewer line. Treatment of 100% gray water by decentralized treatment should be done. Necessary measures should be made to mitigate the
LXXXIV Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.  LXXXV Use of glass may be reduced up to 40% to reduce the electricity consumption and load on air conditioning. If necessary, use high quality double glass with special reflective coating in windows.  LXXXVI Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.  Energy conservation measures like installation of CFLs /TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible like installing solar street lights, common solar water heaters system. Project proponent should install, after checking feasibility, solar plus hybrid non-conventional energy source as source of energy.  LXXXVIII Diesel power generating sets proposed as source of backup power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Use low sulphur diesel. The location of the DG sets may be decided with in consultation with Maharashtra Pollution Control Board.  Noise should be controlled to ensure that it does not exceed the prescribed standards. During nighttime the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.  Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking shoul	LXXXII	
LXXXV reducing devices or sensor based control.  Use of glass may be reduced up to 40% to reduce the electricity consumption and load on air conditioning. If necessary use high quality double glass with special reflective coating un windows.  Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.  Energy conservation measures like installation of CFLs /TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed offisent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercutry contamination. Use of solar panels may be done to the extent possible like installing solar street lights, common solar water heaters system. Project proponent should install, after checking feasibility, solar plus hybrid non-conventional energy source as source of energy.  Diesel power generating sets proposed as source of backup power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DS ests should be equal to the height needed for the combined capacity of all proposed DG sets. Use low sulphur diesel. The location of the DG sets may be decided with in consultation with Maharashtra Pollution Control Board.  Noise should be controlled to ensure that it does not exceed the prescribed standards. During nighttime the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.  XCI  Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.  Opaque wall should meet prescriptive requirement as per Energy C	LXXXIII	
LXXXVI Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.  Energy conservation measures like installation of CFLs /TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid merchy contamination. Use of solar panels may be done to the extent possible like installing solar street lights, common solar water heaters system. Project proponent should install, after checking feasibility, solar plus hybrid non-conventional energy source as source of energy.  Diesel power generating sets proposed as source of backup power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Use low sulphur diesel. The location of the DG sets may be decided with in consultation with Maharashtra Pollution Control Best andards. During nighttime the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.  XC  Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.  Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code, which is proposed to be mandatory for all air-conditioned spaces while it is aspiration for non-air-conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.  XCII  The building should have adequate distance between them to allow movement of fresh air and pa	LXXXIV	
thermal insulation material to fulfill requirement.  Energy conservation measures like installation of CFLs /TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible like installing solar street lights, common solar water heaters system. Project proponent should install, after checking feasibility, solar plus hybrid non-conventional energy source as source of energy.  Diesel power generating sets proposed as source of backup power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets, Use low sulphur diesel. The location of the DG sets may be decided with in consultation with Maharashtra Pollution Control Board.  Noise should be controlled to ensure that it does not exceed the prescribed standards. During nighttime the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.  XC  Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.  Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code, which is proposed to be mandatory for all air-conditioned spaces while it is aspiration for non-air-conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.  XCII  The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air a	LXXXV	
should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible like installing solar street lights, common solar water heaters system. Project proponent should install, after checking feasibility, solar plus hybrid non-conventional energy source as source of energy.  Diesel power generating sets proposed as source of backup power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Use low sulput diesel. The location of the DG sets may be decided with in consultation with Maharashtra Pollution Control Board.  Noise should be controlled to ensure that it does not exceed the prescribed standards. During nighttime the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.  Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.  Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code, which is proposed to be mandatory for all air-conditioned spaces while it is aspiration for non-air-conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.  XCII The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.  Regular supervision of the above and other measures for monitoring should be in place all through the construction phase, so as to avoid disturbance to	LXXXVI	
illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Use low sulphur diesel. The location of the DG sets may be decided with in consultation with Maharashtra Pollution Control Board.  Noise should be controlled to ensure that it does not exceed the prescribed standards. During nighttime the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.  Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.  Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code, which is proposed to be mandatory for all air-conditioned spaces while it is aspiration for non-air-conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.  XCII The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.  XCIII Regular supervision of the above and other measures for monitoring should be in place all through the construction phase, so as to avoid disturbance to the surroundings.  Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.  Six monthly monitoring reports should be submitted to the Regional office MoEF, Bhopal with copy to this	LXXXVII	should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible like installing solar street lights, common solar water heaters system. Project proponent should install, after checking feasibility, solar plus hybrid non-conventional energy source as
noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.  Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.  Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code, which is proposed to be mandatory for all air-conditioned spaces while it is aspiration for non-air-conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.  XCII  The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.  Regular supervision of the above and other measures for monitoring should be in place all through the construction phase, so as to avoid disturbance to the surroundings.  Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.  Six monthly monitoring reports should be submitted to the Regional office MoEF, Bhopal with copy to this	LXXXVIII	illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Use low sulphur diesel. The location of the DG sets may be
avoided. Parking should be fully internalized and no public space should be utilized.  Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code, which is proposed to be mandatory for all air-conditioned spaces while it is aspiration for non-air-conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.  XCII  The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.  Regular supervision of the above and other measures for monitoring should be in place all through the construction phase, so as to avoid disturbance to the surroundings.  Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.  Six monthly monitoring reports should be submitted to the Regional office MoEF, Bhopal with copy to this	LXXXIX	noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply
proposed to be mandatory for all air-conditioned spaces while it is aspiration for non-air-conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.  The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.  Regular supervision of the above and other measures for monitoring should be in place all through the construction phase, so as to avoid disturbance to the surroundings.  Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.  Six monthly monitoring reports should be submitted to the Regional office MoEF, Bhopal with copy to this	XC	
natural light, air and ventilation.  Regular supervision of the above and other measures for monitoring should be in place all through the construction phase, so as to avoid disturbance to the surroundings.  Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.  Six monthly monitoring reports should be submitted to the Regional office MoEF, Bhopal with copy to this	XCI	proposed to be mandatory for all air-conditioned spaces while it is aspiration for non-air-conditioned spaces
construction phase, so as to avoid disturbance to the surroundings.  Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.  Six monthly monitoring reports should be submitted to the Regional office MoEF, Bhopal with copy to this	XCII	
xCIV proponent if it was found that construction of the project has been started without obtaining environmental clearance.  Six monthly monitoring reports should be submitted to the Regional office MoEF, Bhopal with copy to this	XCIII	
	XCIV	proponent if it was found that construction of the project has been started without obtaining environmental
	XCV	

XCVI	Project proponent shall ensure completion of STP, MSW disposal facility, green belt development prior to occupation of the buildings. As agreed during the SEIAA meeting, PP to explore possibility of utilizing excess treated water in the adjacent area for gardening before discharging it into sewer line No physical occupation or allotment will be given unless all above said environmental infrastructure is installed and made functional including water requirement in Para 2. Prior certification from appropriate authority shall be obtained.
XCVII	Wet garbage should be treated by Organic Waste Converter and treated waste (manure) should be utilized in the existing premises for gardening. And, no wet garbage will be disposed outside the premises. Local authority should ensure this.
XCVIII	Local body should ensure that no occupation certification is issued prior to operation of STP/MSW site etc. with due permission of MPCB.
XCIX	A complete set of all the documents submitted to Department should be forwarded to the Local authority and MPCB.
С	In the case of any change(s) in the scope of the project, the project would require a fresh appraisal by this Department.
CI	A separate environment management cell with qualified staff shall be set up for implementation of the stipulated environmental safeguards.
CII	Separate funds shall be allocated for implementation of environmental protection measures/EMP along with item-wise breaks-up. These cost shall be included as part of the project cost. The funds earmarked for the environment protection measures shall not be diverted for other purposes and year-wise expenditure should reported to the MPCB & this department.
CIII	The project management shall advertise at least in two local newspapers widely circulated in the region around the project, one of which shall be in the Marathi language of the local concerned within seven days of issue of this letter, informing that the project has been accorded environmental clearance and copies of clearance letter are available with the Maharashtra Pollution Control Board and may also be seen at Website at http://ec.maharashtra.gov.in.
CIV	Project management should submit half yearly compliance reports in respect of the stipulated prior environment clearance terms and conditions in hard & soft copies to the MPCB & this department, on 1st June & 1st December of each calendar year.
CV	A copy of the clearance letter shall be sent by proponent to the concerned Municipal Corporation and the local NGO, if any, from whom suggestions/representations, if any, were received while processing the proposal. The clearance letter shall also be put on the website of the Company by the proponent.
CVI	The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM. SO2, NOx (ambient levels as well as stack emissions) or critical sector parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.
CVII	The project proponent shall also submit six monthly reports on the status of compliance of the stipulated EC conditions including results of monitored data (both in hard copies as well as by e-mail) to the respective Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB.
CVIII	The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the respective Regional Offices of MoEF by e-mail.

### Maharashtra

- 4. The environmental clearance is being issued without prejudice to the action initiated under EP Act or any court case pending in the court of law and it does not mean that project proponent has not violated any environmental laws in the past and whatever decision under EP Act or of the Hon'ble court will be binding on the project proponent. Hence this clearance does not give immunity to the project proponent in the case filed against him, if any or action initiated under EP Act.
- 5. In case of submission of false document and non-compliance of stipulated conditions, Authority/ Environment Department will revoke or suspend the Environment clearance without any intimation and initiate appropriate legal action under Environmental Protection Act, 1986.
- 6. The Environment department reserves the right to add any stringent condition or to revoke the clearance if conditions stipulated are not implemented to the satisfaction of the department or for that matter, for any other administrative reason.
- 7. Validity of Environment Clearance: The environmental clearance accorded shall be valid as per EIA Notification, 2006, and amendments by MoEF&CC Notification dated 29th April, 2015.
- 8. In case of any deviation or alteration in the project proposed from those submitted to this department for clearance, a fresh reference should be made to the department to assess the adequacy of the condition(s) imposed and to incorporate additional environmental protection measures required, if any.
- 9. The above stipulations would be enforced among others under the Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and Control of Pollution) Act, 1981, the Environment (Protection) Act, 1986 and rules there under, Hazardous Wastes (Management and Handling) Rules, 1989 and its amendments, the public Liability Insurance Act, 1991 and its amendments.
- 10. Any appeal against this Environment clearance shall lie with the National Green Tribunal (Western Zone Bench, Pune), New Administrative Building, 1stFloor, D-, Wing, Opposite Council Hall, Pune, if preferred, within 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.

Shri. Anil Diggikar (Member Secretary SEIAA)

### Copy to:

- 1. SECRETARY MOEF & CC
- 2. IA- DIVISION MOEF & CC
- 3. MEMBER SECRETARY MAHARASHTRA POLLUTION CONTROL BOARD MUMBAI
- 4. REGIONAL OFFICE MOEF & CC NAGPUR
- 5. MUNICIPAL COMMISSIONER PUNE
- 6. MUNICIPAL COMMISSIONER SATARA
- 7. REGIONAL OFFICE MPCB PUNE
- 8. REGIONAL OFFICE MIDC PUNE
- 9. MAHARASHTRA STATE ELECTRICITY DISTRIBUTION CO. LTD
- 10. COLLECTOR OFFICE PUNE
- 11. COLLECTOR OFFICE SATARA
- 12. COLLECTOR OFFICE SOLAPUR